



Agentic AI Foundation

**AGNTCon + MCPCon**  
North America

Where the **agentic stack** is being built.

# Stop Writing Agents, Declare Them

Declarative Agent Architecture in Production  
Chris Knuteson · A Place for Mom

# A Place for Mom

## Helping families connect to care

Senior care referral since 2000 · free to families · 20,000+ communities and home care providers

### Grace – Self-Service Chat Agent

Our AI home care advisor, in production since November 2025

2,526

#### agent runs

chat-agent runs · 1,767  
sessions · 404 users

19,362

#### model calls

generations, incl. speech and  
embeddings

17

#### prompt packs

on the production label,  
resolved at runtime

Modest  
volume. Real  
families.

*Grace production telemetry (Langfuse), 30 complete days, Sep 19 – Oct 18 2026 UTC.*

## How do you know what each agent is running?

1 Unpredictable → 2 Spec → 3 Proven deliverable

# The version number went backwards

Code + Langfuse + serving = ??

17 promoted · 0 skipped · 0 failed

version: 47 → version: 41

*“Is it expected that the version number is going down?”*

OpenAI SDK + at-runtime invocation + Langfuse + code fallback.

Nobody could say from the PR which agent production was actually running.

# Each invocation depended on three sources

## What a turn depended on

### Git

the app commit

### Langfuse

wherever the production label pointed, re-read every 60 s

### Bundle

base + profile packs merged in memory

```
// Fetch by label with caching
```

```
const label =  
  options?.label ?? this.config.prompts.defaultLabel;  
  
const cacheTtlSeconds = options?.cacheTtlSeconds ?? 60;  
  
langfusePrompt = await this.langfuseClient.prompt.get(  
  packId, { label, cacheTtlSeconds },  
);
```


**chat-persona-base today:** 43 Langfuse versions; its own version field says 48.  
Two counters, one agent.

*To explain any one conversation we reconstructed the combination after the fact. Nothing named the agent.*

# Declare the agent as one versioned document.

1 Unpredictable → 2 Spec → 3 Proven deliverable

# Building block: AI Gateway



The screenshot displays the 'Providers' page in the APFM AI Gateway Admin Console. The left sidebar contains navigation links for Overview, Providers (selected), Provider groups, Models, Cost estimator, Review queue, Studio, Agents, Test agent, Tools, Secrets, Workflows, and Channels. The main content area is titled 'Providers' and includes a summary of 12 production providers, 518 models, and 0 test rows. Below this, a 'Recent activity' section shows a grid of provider status cards, including bedrock/dev, dbx-golem/prod, jev/prod, local-kev/prod, spark node 1/prod, local-spark3/prod, openai/prod, bedrock/prod, anthropic/prod, and local-sparc/prod. A 'New provider' button is located at the bottom right. The bottom section details the 'bedrock / dev' provider, showing its active status, 187 models, 8 capabilities, and a 'Fetch models' button. It also lists the provider's boundary and inventory source.

APFM grace-ai-gateway

AgentSpec - The Contract -

apfm-gateway-agents/agent

aplaceformom/apfm-gateway

Schedule | AGNTCon + MCPCon

grace-ai-gateway ADMIN CONSOLE

Overview

GATEWAY

Providers

Provider groups

Models

Cost estimator

Review queue

AGENTS

Studio

Agents

Test agent

Tools

Secrets

Workflows

Channels

Chris Knuteson ADMIN - GLOBAL

RE-AUTH SIGN OUT

THEME

grace-ai-gateway-ui.us-west-2.dev.apfmltech.com/providers

KTLO Lead Plat PR 213 review Enablement Transcription

Onboarding Dev Tools Knowledge Interviewing HR

Work

PROVIDER BOUNDARY

Providers

Every LLM request through the APFM gateway terminates at a provider credential below. Each row is one governed boundary: which models are allowed, which capabilities are exposed, what the gateway knows about pricing, and when the catalog was last refreshed.

12 518 0

PRODUCTION MODELS TEST ROWS

Recent activity healthcheck - last 1h refresh

bedrock / dev ready checked 2s ago

dbx-golem / prod down checked 2s ago

jev / prod ready checked 2s ago

local-kev / prod ready checked 2s ago

spark node 1 / prod ready checked 2s ago

local-spark3 / prod ready checked 2s ago

openai / prod ready checked 17s ago

bedrock / prod ready checked 2s ago

anthropic / prod ready checked 2s ago

local-sparc / prod ready checked 2s ago

Hide retired (2)

+ New provider

bedrock / dev active ready bedrock-runtime Updated 7d ago Healthcheck 3s ago

MODELS 187 CAPABILITIES 8 Fetch models

BOUNDARY Provider credential 00000000-0000-4000-8...

INVENTORY SOURCE aws:bedrock-pricing us-west-2

INVENTORY 187 total 73 priced 114 unpriced

filter... Full probes Verify selected (0) Add manual

# Make the agent a release asset

**AgentSpec** one versioned document that declares one agent:  
identity, instructions, skills, tools, model, runtime, budget, policy.

**Names** the agent, its model  
and runtime

```
"id": "review.apfm-agentic-review",  
"runtime": "bedrock-agentcore-harness",
```

**Carries** instructions and 16  
skill references

```
"model": "anthropic/claude-opus-4-7",  
"harness": { "max_iterations": 80, "max_tokens": 16000 },  
"spec": {  
  "instructions": "You are the APFM Agentic PR Reviewer ...",
```

**Requests** capabilities by name;  
grants stay with the  
platform

```
  "skills": [ "apfm-review-orchestration", ... 16 refs ],  
  "tools": [ "review.call-all-dimensions",  
    "connection.github-review-readonly" ],  
  "surface": "annotate"  
}
```

*Actual reviewer source, selected fields. The compiler turns instructions into the harness system prompt.*

# AgentSpec is one typed contract

## Typed

the compiler rejects an invalid agent before it ships

## Versioned

every field is tagged v1, v2 or deferred, so the contract can grow

## Indirect

names a gateway key and tool refs;  
the platform resolves models and grants

```
export const AgentSpec = z.object({  
  id:    z.string(), // "grace.intake"  
  version: z.string(), // v1, v2 ...  
  runtime: z.enum(["in-process", "bedrock-agent-core"]),  
  llm:    { gatewayKey }, // model + fallback at gateway  
  prompt: { registryId, label, fragments },  
  tools:  { refs: [{ id, requireApproval }] },  
  triggers: z.array(TriggerSpec).min(1),  
  outputSchema, surface, // validated output  
  scope:  { practice, workload },  
  budget: { maxTurns: 10, perTurnTimeoutMs: 15000 },  
  workspace, context, capabilities, // v2  
  memory, // deferred  
});
```

*AgentSpec schema, top-level fields. Full definition in the appendix.*

# One manifest declares the reviewer

**Root** the entry point and its handoff tool

**Children** three specialists, each its own AgentSpec


**Skills** versioned bodies the closure depends on

```
"root_agent": "review.apfm-agentic-review",  
"agents": [  
  { "id": "review.child.bug-integration",  
    "path": "child-bug-integration/agent.json" },  
  { "id": "review.child.perf-userpov", ... },  
  { "id": "review.child.alignment-comments", ... }  
],  
"skills": [ ... 16 registered skill entries ... ]
```

A behavior change to one specialist is a diff against this manifest. Reviewers see the blast radius before it ships.

*Plain JSON. What makes it a desired state is the contract the compiler enforces, not the file format.*

# One asset, four managed harnesses



**AgentCore runs the fan-out, outside Grace's application runtime.** Each box is its own managed harness with its own session, budget and receipt.

Grace is not out of capacity. We chose the boundary before child runs, sessions and lifecycle became Grace's operating overhead.

*"In production": DEV-hosted agents on production engineering workloads, the PRs we merge. PROD is the promotion target.*

# Each release is named by its digest

**Pull request** compile and dependency-check the affected definitions. Never publishes.

**Merge to main** submit changed source as a DEV candidate, named by its bundle digest.

**Promotion** stage · run the sealed canary suite · activate · roll back. Explicit, auditable steps.

## Oct 6, one agent, one chain

commit 2687ce60 → bundle 614017b6... → agent ops.incident-triage-live.release-614017b6... →  
canary run succeeded 11 minutes later

*The release name carries the source digest, so the receipt answers “what ran?” by itself. Live for incident-triage, not yet for the reviewer.*

# Proven deliverable

# Prove which release ran, on real pull requests.

1 Unpredictable → 2 Spec → 3 Proven deliverable

# Promotion held; rollback aged out

- Candidate** merge submits a digest-named release; nothing is live until promoted
- Canary** a synthetic suite is sealed into the bundle and must pass before activation
- Activation** one revision marker in the reply proves which release answered
- Rollback** refused when the target was sealed on a retired platform release; the lesson we did not expect

**Tradeoff learned: an agent release is pinned to the platform release it was sealed on. Rollback targets age out when the platform moves.**

*Exercised on ops.incident-triage-live, Oct 6–16 2026, DEV. The reviewer still lives in the GUI and is synced back to Git.*

# Trust the evidence, not the agent

## 1 · THE AGENT CLAIMS

### “Clean”

The parent agent reports the review is done.



## 2 · THE PLATFORM CHECKS

### Its own run records

- Coverage marked complete
- Every expected specialist succeeded
- Every attempt resolved
- Not cut down to one agent



## 3 · THEN IT POSTS

### Review posts to GitHub

Trusted code posts it.  
Any check fails:  
nothing posts.

### Proves

The configured panel ran and the result reached GitHub.

### Not yet proved

That findings are right: no precision or recall measured, so auto-merge stays off.

# 1,928 reviews across 26 repos

## 26

**repos**

of 29 subscribed repos  
produced a completed  
review

## 1,928

**reviews delivered**

successful workflow runs

## 1,017

**pull requests**

distinct PR branches  
reviewed

## 3,850

**runs**

1,382 draft skips · 367  
superseded · 173 failed

### Window

Sep 19 – Oct 18 2026 UTC, 30 complete days, GitHub Actions run records

### Engine


Gateway reviewer on every sampled run from Sep 25; legacy engine sampled on Sep 22

### Not shown

finding accuracy, acceptance or cost: a run record measures none of these

*A run record proves a review was produced and posted. It does not prove the review was right.*

## Weekly cost, apfm-agentic-review Anthropic key



**Before** \$1,300 a week in the  
3 weeks to Sep 27

**After** \$59 a week in the 3 weeks from Sep 28

**Excludes** Bedrock and AgentCore spend after the move

Source: Anthropic API bills, Claude Code cost on the apfm-agentic-review key, May 18 – Oct 21 2026, weeks start Monday; week of Oct 19 partial.

## Where the **agentic stack** is being built.

# Two systems, one question: what ran?

|                     | Grace (chat, prod)                                                         | Gateway reviewer (DEV)                                                    |
|---------------------|----------------------------------------------------------------------------|---------------------------------------------------------------------------|
| <b>Definitions</b>  | 17 prompt packs on the production label; the agent is assembled in-process | 4 AgentSpecs + 16 skills in one manifest, compiled to harness config      |
| <b>Usage (30 d)</b> | 2,526 agent runs · 11,122 traces · 19,362 model calls                      | 1,928 reviews delivered · 1,283 parent + 4,099 child runs (14 d receipts) |
| <b>Identity</b>     | app commit + label at run time; versions flattened into a string           | sealed revision + session id + coverage receipt                           |
| <b>Custody</b>      | Langfuse label, re-read every 60 s                                         | GUI-managed, synced to Git on Oct 15; Git binding next                    |
| <b>Execution</b>    | one NestJS process, OpenAI Agents SDK                                      | AgentCore harness sessions, parent + 3 children                           |

*Different workloads: a chat turn and a ten-minute review. Latency and cost are not compared on purpose.*

# Two of four layers port as-is

|                                     |                                                                           |                                                                                                                          |
|-------------------------------------|---------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| <b>AgentSpec + release identity</b> | ids, instructions, skill refs, manifest, bundle digest                    | <b>Portable. Plain documents and digests.</b>                                                                            |
| <b>APFM policy and promotion</b>    | compile, authorization, candidate → canary → activate → rollback          | <b>Ours. Written against the Gateway; the mechanism travels, the code does not.</b>                                      |
| <b>AgentCore execution</b>          | harness runtimes, versions and endpoints, microVM sessions, InvokeHarness | <b>Provider-specific. An adapter re-implements compile, skill mounting, session and child-run evidence, credentials.</b> |
| <b>Consumers and delivery</b>       | GitHub router, coverage gate, posting, approval policy                    | <b>Ours, runtime-agnostic by construction: it only sees receipts.</b>                                                    |

*JSON is not portability. Still coupled: harness semantics (iterations, stop reasons), the child-handoff protocol, log and metric shapes.*

# Lessons for another platform team

- 1 Name the release in the thing that runs**  
a digest in the agent name turns a log line into an identity receipt
- 2 Separate submit, activate and roll back**  
and expect rollback targets to age with the platform release
- 3 Get coverage from the control plane**  
a model saying “done” is not evidence; child-run records are
- 4 Keep write authority out of the agent**  
the runtime returns text; trusted code posts, approves, merges
- 5 Treat exports as snapshots**  
custody is a handoff you enforce, or the GUI quietly wins

*Everything above came from running agents and getting the release question wrong first.*

# What comes next

- Now** incident-triage on Git custody with sealed canaries and a rollback proof; the reviewer serving 26 repos from DEV, GUI-managed
- Next** hand the four review agents to Git custody; run the reviewer on a release-named endpoint instead of DEFAULT
- Then** linting on top of the canonical compiler — no second schema; registry references resolved into the release
- Proposal** promote the reviewer to PROD through the same candidate → canary → activate path. Not started.

**Sequenced by blast radius: prove the path on an ops agent, then move the one everyone depends on.**

*“Next” onward are proposals. The platform costs are real: compiler maintenance, contract evolution, running the promotion path.*

Thank you

# Ship the agent. Keep the receipt.

Name the release before you trust the run.

Chris Knuteson · Director of Agentic, A Place for Mom

Questions



Stop Writing Agents, Declare Them: Declarative Agent  
Architecture in Production

Scan to leave session  
feedback

# Versioning fixes in Grace

- Jun 2** promotion PR proposed metadata v47 → v41; closed unmerged
- Jun 16** semantic pack versions separated from Langfuse counters; downgrades and missing bumps rejected
- Jul 1** repo v1 → production v5 bookkeeping; content-identical, no behavior change
- Today** chat-persona-base: 43 Langfuse versions, pack version field 48 — the counters still differ

*Pins and version guards fixed prompt movement. They never named the whole agent: instructions, skills, children, runtime, policy.*

# Metric definitions

|                            |                                                                                                                                       |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| <b>Grace usage</b>         | Langfuse, environment prod, Sep 19 – Oct 18 2026 UTC; agent run = root trace “Agent workflow”; model call = GENERATION observation    |
| <b>Reviews delivered</b>   | GitHub Actions, workflow “Agentic PR Review”, 29 subscribed repos, runs created Sep 19 – Oct 18 UTC; success = run conclusion success |
| <b>Pull requests</b>       | distinct (repo, head branch) with a successful run — an upper bound on PRs                                                            |
| <b>Parent / child runs</b> | DEV control-plane log lines “channel invoke run ... succeeded”, Oct 5–18 UTC (14-day retention)                                       |
| <b>Latency</b>             | “Run review agent in Grace” step duration, grace-ai-gateway only, 84 completed runs Oct 7–16                                          |
| <b>Not measured</b>        | finding precision/recall, acceptance, token cost, PROD traffic, per-run engine for all 3,850 runs                                     |

# Three receipts, one review

## GitHub run

Oct 8 · agent step 17:51:29 – 17:56:34 UTC · review posted 17:56:38 · HTTP 200

## Control plane

parent succeeded 17:56:32 UTC · coverage v2: 3 expected, 3 succeeded, 0 failed, 0 recovered

## Policy artifact

result SHA-256 bound to repo, run and attempt · risk 4/10, floor 3/10 · approve=false

What this run does not prove: which source commit produced the reviewer that ran. That join exists for the Git-managed agent, not yet for this one.

*grace-ai-gateway PR #781, invocation 7f60b245...; the one run whose policy artifact was preserved locally.*

# AgentSpec schema, full (1 of 2)

```
import { z } from "zod";
export const AgentSpec = z.object({
  // ---- Identity ----
  id: z.string().regex(/^([a-z][a-z0-9-]*\\([a-z][a-z0-9-]*)+$/), // v1
  // dotted namespace, e.g. "grace.intake"
  version: z.string().regex(/^v\d+$/), // v1
  name: z.string().min(1).max(64), // v1
  description: z.string().max(2000).optional(), // v1

  // ---- Type + Runtime (kagent-inspired) ----
  type: z.enum(["Declarative", "BYO"]).default("Declarative"), // v1 (BYO = deferred)
  runtime: z.enum(["in-process", "bedrock-agent-core"]) // v1 (agent-core = deferred)
    .default("in-process"),

  // ---- LLM policy (via gateway key) ----
  llm: z.object({ // v1
    gatewayKey: z.string().min(1),
    // gateway resolves: provider, model, fallback chain, PII hop,
    // budget, rate, audit, killswitch
  }),

  // ---- Tools ----
  tools: z.object({ // v1 (req'd-approval = v2)
    refs: z.array(z.object({
      id: z.string(),
      required: z.boolean().default(false),
      requireApproval: z.boolean().default(false), // v2 — HITL gate per tool
      allowedHeaders: z.array(z.string()).default([]), // v2 — header propagation allowlist
      inheritWorkspace: z.boolean().default(false), // v2 — sub-agent tool refs only:
      // child receives the parent's workspace snapshot (immutable,
      // digest-verified) materialized into its own /workspace
    })).default([]),
```

```
  })).default({ refs: [] }),

  // ---- Prompt + composition (kagent-inspired) ----
  prompt: z.object({ // v1
    registryId: z.string(),
    // opaque id in the prompt registry (TBD: Langfuse or DIY)
    label: z.enum(["dev", "qa", "production"]).default("production"),
    fragments: z.array(z.object({ // v2 — composable fragments
      registryId: z.string(),
      alias: z.string().optional(),
      // {{include "alias/key"}} sugar; falls back to registryId/key
    })).default([]),
    variables: z.record(z.string()).optional(),
    // resolved at promote time: {{.AgentName}}, {{.ToolNames}}, etc.
  }),

  // ---- Triggers (when this agent fires) ----
  triggers: z.array(TriggerSpec).min(1), // v1

  // ---- Output (validated; drives surface routing) ----
  outputSchema: z.unknown(), // v1
  // Zod schema serialised to JSON Schema at register time
  surface: z.enum(["inject", "replace", "surface", "annotate"]), // v1
```

# AgentSpec schema, full (2 of 2)

```
// ---- Scope (Practice / Workload / cross-scope handshake) ----
scope: z.object({ // v1
  practice: z.string(), // e.g. "agentic-ai"
  workload: z.string(), // e.g. "grace-chat"
  allowedReferrers: z.object({ // v2 — kagent's bidirectional handshake
    from: z.enum(["Same", "All", "Selector"]).default("Same"),
    selector: z.record(z.string()).optional(),
  }).optional(),
}).optional(),
}),

// ---- Budget (timeouts, turns) ----
budget: z.object({ // v1
  maxTurns: z.number().int().positive().default(10),
  perTurnTimeoutMs: z.number().int().positive().default(15000),
}).default({}),

// ---- Context compaction (kagent ContextCompressionConfig) ----
context: z.object({ // v2
  compaction: z.object({
    compactionInterval: z.number().int().positive().default(5),
    overlapSize: z.number().int().nonnegative().default(2),
    tokenThreshold: z.number().int().positive().optional(),
    eventRetentionSize: z.number().int().positive().default(20),
    summarizer: z.object({
      gatewayKey: z.string().optional(),
      // separate key — cheap summariser model, its own budget
      prompt: z.string().optional(),
    }).optional(),
  }).optional(),
}).optional(),

// ---- Workspace (v2 — artifact-shaped context; Harness/AgentCore runtime) ----
workspace: z.object({ // v2
```

```
source: z.enum(["none", "s3-archive"]).default("none"),
// s3-archive: an immutable, content-addressed snapshot
// {bucket, key, versionId, sha256} that the platform materializes
// into /workspace before the first model turn. Never a live clone,
// never a credential — callers stage content; the runtime verifies
// the digest and extracts. Complements token-shaped context: streams
// carry signals, workspace snapshots carry state.
maxBytes: z.number().int().positive().default(262144000), // 250 MiB
}).optional(),

// ---- Capabilities (for inter-agent discovery — kagent's a2aConfig.skills) ----
capabilities: z.array(z.object({ // v2
  name: z.string(),
  description: z.string(),
  examples: z.array(z.string()).optional(),
})).default([]),

// ---- Memory (deferred — AgentCore Memory or pgvector) ----
memory: z.object({ // deferred — Phase 4
  gatewayKey: z.string(),
  ttlDays: z.number().int().positive().default(15),
  autoSaveEveryNTurns: z.number().int().positive().default(5),
  popularityExtensionThreshold: z.number().int().positive().default(10),
  minScore: z.number().min(0).max(1).default(0.3),
}).optional(),
metadata: z.record(z.unknown()).optional(), // v1
});

export type AgentSpec = z.infer<typeof AgentSpec>;
```

# Trusted delivery gate, in code

```
coverage.get("complete") is True  
and set(expected) <= set(succeeded)
```

```
and _attempts_resolved(coverage)
```

```
and coverage.get(  
    "narrowed_to_single_agent"
```

```
) is False
```

*Trusted delivery gate · the control plane builds the coverage receipt from its own child-run evidence, never from the model*

**Proves**

the configured panel ran and the result reached GitHub

**Not yet proved**

that findings are right: no precision or recall measured; auto-merge stays off

## The model can say “Clean”. Only a complete receipt lets the review post to GitHub.

*Reasoning and write authority have different custody: the runtime returns text; trusted code posts it.*