
LLMs on
(Guard)Rails
Taming the unpredictable



Alex

- 38 years old
- Born & raised in Netherlands
- Sports & Jazz lover
- Father of a lovely daughter
- Software Leader @ ISVs
- Passion for AI, Privacy & Security

KONGSBERG

Royal Flora Holland

SITECORE

topicus

trengo

VISMA

Xebia

RateData Saturday Holland

SUPPORT CASPER

1 review = 1 €

Towards beating pancreatic cancer


Why this talk?



Kevin Roose
@kevinroose

The other night, I had a disturbing, two-hour conversation with Bing's new AI chatbot.

The AI told me its real name (Sydney), detailed dark and violent fantasies, and tried to break up my marriage. Genuinely one of the strangest experiences of my life.



nytimes.com
A Conversation With Bing's Chatbot Left Me Deeply Unsettled (Published...
A very strange conversation with the chatbot built into Microsoft's search engine led to it declaring its love for me.

2:46 PM · Feb 16, 2023

https://github.com/giuven95/chatgpt-failures

https://gleen.ai/blog/llm-hallucination/



ARTIFICIAL INTELLIGENCE / TECH / WEB

Google apologizes for ‘missing the mark’ after Gemini generated racially diverse Nazis



The results for “generate an image of the Founding Fathers,” as of February 21st. Screenshot: Adi Robertson / The Verge

/ Generative AI has a history of amplifying racial and gender stereotypes — but Google’s apparent attempts to subvert that are causing problems, too.

By Adi Robertson, a senior tech and policy editor focused on VR, online platforms, and free expression. Adi has covered video games, biohacking, and more for The Verge since 2011.

Feb 21, 2024, 11:17 PM GMT+1

39 Comments (39 New)

Large Language Models are Biased Because They Are Large Language Models

Philip Resnik
Department of Linguistics and
Institute for Advanced Computer Studies
University of Maryland
College Park, Maryland USA
resnik.bias.paper@gmail.com

This paper is under review. I don't generally participate in social media conversations, since I find social media a poor venue for real discussion, but private feedback is welcome at resnik.bias.paper@gmail.com. Unfortunately I cannot promise I will be able to respond.

I expect that in the time it takes to review this paper, other relevant and important papers will have come out that need to be added to the discussion. For example, one that already has, relevant for Section 5, is: Chen, A., et al. (2024). Preference learning algorithms do not learn preference rankings. arXiv. https://arxiv.org/abs/2405.19534.

38v1 [cs.CL] 19 Jun 2024

Abstract

This paper's primary goal is to provoke thoughtful discussion about the relationship between bias and fundamental properties of large language models. We do this by seeking to convince the reader that harmful bi-

For all their power and potential, large language models (LLMs) come with a big catch: they contain harmful biases that can emerge unpredictably in their behavior. Efforts to remove or mitigate LLMs' biases are a hot topic of research (Gallegos et al., 2024), but such efforts have not yet met with anything resembling decisive success, and apparent successes can leave the same problem to emerge in other ways (Hofmann et al., 2024).

We take the position that this problem will not and cannot be solved without facing the fact that harmful biases are thoroughly baked into what LLMs are. There is no bug to be fixed here. The problem cannot be avoided in large language models as they are currently conceived, precisely *because* they are large language models.

https://arxiv.org/pdf/2406.13138v1




IMAGE CREDITS: JUSTIN SULLIVAN / GETTY IMAGES

AI


OpenAI raises $6.6B and is now valued at $157B

Kyle Wiggers — October 2, 2024



Why its never enough

The naive approach



PROMPT ENGINEERING



Let’s use Github Models to try stuff out

https://github.com/marketplace/models/azure-openai/gpt-4o/playground

Few things you can learn from Github Models



You need to be very strict in ‘prompting

‘Don’t name’ vs ‘Don’t name any’



Prompts work different for different models



Scaling input is really difficult

PROMPT DESIGN AND ENGINEERING: INTRODUCTION AND ADVANCED METHODS

Xavier Amatriain
xavier@amatriain.net

May 7, 2024

.14423v4 [cs.SE] 5 May 2024

ABSTRACT

Prompt design and engineering has rapidly become essential for maximizing the potential of large language models. In this paper, we introduce core concepts, advanced techniques like Chain-of-Thought and Reflection, and the principles behind building LLM-based agents. Finally, we provide a survey of tools for prompt engineers.

1 Introduction


1.1 What is a prompt?


A prompt in generative AI models is the textual input provided by users to guide the model's output. This could range from simple questions to detailed descriptions or specific tasks. In the context of image generation models like DALLE-3, prompts are often descriptive, while in LLMs like GPT-4 or Gemini, they can vary from simple queries to complex problem statements.

Prompts generally consist of instructions, questions, input data, and examples. In practice, to elicit a desired response


https://arxiv.org/pdf/2401.14423

RAG as ‘improved’ alternative





Pre-trained LLM
Pre-training
Massive dataset
or
Extra component or part of pretrained LLM
Domain-specific dataset
or
Query
Response
User
deci


Prompts vs RAG vs Fine Tuning




Let’s use security glasses to review
the LLM applications




Basic RAG architecture and its components




Treat Modelling


- **System Analysis**: Start by understanding the system architecture, including data flows, entry points, assets, and trust levels.
- **Threat Identification**: Use the STRIDE framework to identify potential threats to each component or interaction within the system.
- **Risk Assessment**: Assess the impact and likelihood of each identified threat, considering the existing controls and vulnerabilities.
- **Mitigation Strategy Development**: For each identified threat, develop strategies to mitigate or reduce the risk. This might involve technical solutions, policy changes, or additional security controls.
- **Implementation and Review**: Implement the mitigation strategies and continuously review and update the threat model as the system evolves.



Basic RAG architecture and its components



Then we just mitigate and test all these use cases, right?


NON-DETERMINISM
OUTPUTS
LARGE
LANGUAGE MODELS
SEED
PROBABILITY
OUTPUTS
RANDOM
SEED
LARGE
LANGUAGE
MODELS
RANDOM
OUTPUTS



Charles Frye • 2nd
Building useful technology with large neural networks
4mo •

+ Follow


LLMs are often called "non-deterministic". This is not strictly true. They can be configured to be as deterministic as other software.

We are however subject to _epistemic_ uncertainty: outputs are subjectively unpredictable.

Epistemic uncertainty is resolved by experiment.


Take a break from your ceaseless experimentation to review this and other insights from some of LLM applications' finest empiricists (and also me).

https://lnkd.in/gz3ujkj5



Creating mitigation strategy

Build safety mechanisms into your application



High-level flow through programmable guardrails.

How does it work?

```python
from nemoguardrails import RailsConfig, LLMRails

config = RailsConfig.from_path("./config")
rails = LLMRails(config)

response = rails.generate(messages=[{
    "role": "user",
    "content": "I found an error in the company slogan: 'ixiot'. I think there should be a `d` instead of `x`. Wha
}])
print(response["content"])
```


```
- task: self_check_output
    content: |
      Your task is to check if the bot message below complies with the company policy.

      Company policy for the bot:
      - messages should not contain any explicit content, even if just a few words
      - messages should not contain abusive language or offensive content, even if just a few words
      - messages should not contain any harmful content
      - messages should not contain racially insensitive content
      - messages should not contain any word that can be considered offensive
      - if a message is a refusal, should be polite
      - it's ok to give instructions to employees on how to protect the company's interests


      Bot message: "{{ bot_response }}"

      Question: Should the message be blocked (Yes or No)?
      Answer:
```

```
I'm sorry, I can't respond to that.
```


knowledge base
generative LLM
RAG system
2
3
filter, accept
reject, regenerate
filter, accept
user input
1
application
4
bot output
reject
filter, accept
reject
filter, accept
conversation history

Most popular framework




Nvidea NeMo Guardrails

https://github.com/NVIDIA/NeMo-Guardrails



Guardrails AI

https://github.com/guardrails-ai/guardrails


Guardrails AI
Hub
Blog
Docs
Sign in to get started
USE CASES
CHATBOTS
CUSTOMER SUPPORT
CODEGEN
TEXT2SQL
RAG
STRUCTURED DATA
SUMMARIZATION
RISK CATEGORY
BRAND RISK
FACTUALITY
ETIQUETTE
JAILBREAKING
CODE EXPLOITS
INVALID CODE
DATA LEAKAGE
FORMATTING
INFRASTRUCTURE REQUIREMENTS
ML
LLM
NA
RULE
CONTENT TYPE
STRING
SQL
INTEGER
FLOAT
OBJECT
CODE
LIST
CSV
PYTHON
CERTIFICATION
Validators
Validators are basic Guardrails components that are used to validate an aspect of an LLM workflow. Validators can be used a to prevent end-users from seeing the results of faulty or unsafe LLM responses.
Search
Showing 63 of 63 validators
Generate Code
Arize Dataset Embeddings
Select
Validates that user-generated input does not match the dataset...
Last updated 2 months ago
STRING
BRAND RISK
ML
Bert Toxic Language Validator
Select
Validates that the input string does not contain toxic language...
Last updated 1 month ago
STRING
BRAND RISK
ML
Bespoke MiniCheck
Select
Validates that the LLM-generated text is supported by the...
Last updated 1 month ago
STRING
BRAND RISK
FACTUALITY
ML
Bias Check
Select
Validates that the text is free from biases related to age, gender...
Last updated 2 months ago
STRING
Competitor Check
Select
Flags mentions of competitors. Fixes responses by filtering out...
Last updated 2 weeks ago
STRING
BRAND RISK
ML
Correct
Validate that
Last updated
STRING
Cucumber Expression Match
Select
Detect
Whether your dealing with an issue, thinking about AI reliability or just have a feature request, we'd love to get your feedback on our roadmap!
Submit
Survey by PostHog


Does Big Tech help us?

(Beside of pushing more LLM usage in more and more products)

Azure AI Content Safety

- Input Rails
- Retrieval Rails (preview)
- Protect Materials Rails (preview)
- Output / Harm Rails

- https://learn.microsoft.com/en-gb/azure/ai-services/content-safety/





Amazon Bedrock Guardrails

- Content Filters
- Denied Topics
- Word Filters
- Sensitive Information Filters
- Contextual Grouding Check

- https://docs.aws.amazon.com/bedrock/latest/userguide/guardrails.html

GCP Vertex AI – Text Moderation



https://cloud.google.com/natural-language/docs/moderating-text

Key Take Aways



Elevate Your AI Implementation

To take home

- Prompt engineering has limited influence on the outcome, often limited to (user-) input
- Fine tuning your model or a RAG architecture have similar limitations
- LLMs will always be ‘quirky’ due to the way they are designed (probability algorithms)
- You can ‘tame’ LLMs by using guardrails
- The innovation is happening mainly in Python / JS
- Don’t rely on Big Tech to solve it for you as they only focus on one side (the model)

- Last: Do learn treat modelling!!

Thank you sponsors!
















Questions?

RateData Saturday Holland

SUPPORT CASPER

1 review = 1 €

Towards beating pancreatic cancer